

APPENDIX 2B TO TSC 2020-1 - GASUNIE TRANSPORT SERVICES

Release 1, 01-01-2020

Quality and pressure specifications - exit points

EXIT POINTS		Wobbe minimum	Wobbe maximum	Calorific value minimum	Calorific value maximum	O2 content maximum	CO2 content maximum	sulphur content in H2S maximum	mercaptan sulphur content maximum	total sulphur content maximum	water dewpoint	potential hydrocarbon liquid content max.	temperature exit gas minimum	temperature exit gas maximum	min. gauge pressure	max. gauge pressure
		<i>kWh/m3(n)</i>	<i>kWh/m3(n)</i>	<i>kWh/m3(n)</i>	<i>kWh/m3(n)</i>	<i>mol %</i>	<i>mol %</i>	<i>mg/m3(n)</i>	<i>mg/m3(n)</i>	<i>mg/m3(n)</i>	<i>°C at 72 bar(e)</i>	<i>mg/m3 (n) T ≥ -3 °C at any pressure</i>	<i>°C</i>	<i>°C</i>	<i>bar(e)</i>	<i>bar(e)</i>
Export stations																
300131	Hilvarenbeek	The gas quality specifications laid down in the Dutch Gas Act apply (Regeling gaskwaliteit *)													49.0	66.2
300132	Zevenaar														49.0	66.5
300133	Winterswijk														49.0	66.5
300138	Tegelen														29.0	66.2
300139	Bocholtz														49.0	66.2
300140	Dinxperlo														3.0	16.0
300141	Haanrade														14.7	39.2
300142	Vlieghuis														24.0	66.5
300145	Oude Statenzijl (OGE)														58.2	73.0

* Regeling Gaskwaliteit means the regulation of the Minister of Economic Affairs dated 11 July 2014, nr. WJZ/13196684 as may be amended from time to time